

Amendments to Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (previously presented) An image pickup apparatus comprising:
 - a shaking motion detecting section for detecting a shaking motion of the image pickup apparatus and for outputting a shaking motion detection signal indicating the shaking motion of the image pickup apparatus;
 - an image forming section for forming an optical image by focusing light incident to the image pickup apparatus;
 - an image pickup section for converting the optical image formed by the image forming section into electric video information; and
 - a locus calculating section for obtaining locus information indicating a locus of the shaking motion of the image pickup apparatus based on at least the shaking motion detection signal output from the shaking motion detecting section, wherein the locus calculating section determines whether or not an amount of temporal change in the shaking motion of the image pickup apparatus is larger than a predetermined threshold value, and determines a number of samples in accordance with the determination result.
2. (previously presented) The image pickup apparatus according to claim 1, wherein the locus calculating section obtains, as the locus information, information indicating a change in the shaking motion detection signal during a predetermined period of time.
3. (previously presented) The image pickup apparatus according to claim 1, wherein the shaking motion detecting section includes an angle velocity sensor, and the locus calculating section obtains angle information by integrating an output from the angle velocity sensor, and obtains, as the locus information, information indicating a change in the angle information during a predetermined period of time.
4. (previously presented) The image pickup apparatus according to claim 3, wherein the angle velocity sensor is a vibration gyroscope having a plurality of vibration frequencies which are different from each other.

5. (previously presented) The image pickup apparatus according to claim 1, wherein the locus calculating section obtains, as the locus information, information indicating a locus weighted by the shaking motion of the image pickup apparatus.
6. (previously presented) The image pickup apparatus according to claim 1, wherein the locus calculating section obtains, as the locus information, a point spread function PSF.
7. (Cancelled).
8. (previously presented) The image pickup apparatus according to claim 1, further comprising: an output section for generating data in an Exif format by adding the locus information to the video in-formation, and for outputting the data in the Exif format.
9. (previously presented) The image pickup apparatus according to claim 1, wherein the locus calculating section obtains the locus information based on at least focus information, zoom information, and the shaking motion detection signal.
10. (previously presented) The image pickup apparatus according to claim 1, further comprising: an electronic shaking motion correcting section for performing a calculation processing on the locus information and the video information, so as to obtain corrected video information which is subjected to the correction of the shaking motion.
11. (previously presented) The image pickup apparatus according to claim 10, wherein the electronic shaking motion correcting section determines whether or not the shaking motion detection signal is larger than a predetermined threshold value, and when it is determined that the shaking motion detection signal is larger than the predetermined threshold value, the electronic shaking motion correcting section does not correct the shaking motion in the video information.
12. (previously presented) The image pickup apparatus according to claim 10, wherein the calculation processing includes a Fourier transform, a Fourier inverse transform, or a processing using a two-dimensional filter.
13. (previously presented) The image pickup apparatus according to claim 10, wherein the locus information includes a locus function h , and

the calculation processing includes a calculation of a Fourier transform of h or a calculation using a result of the Fourier transform of h , or

the calculation processing includes a calculation of a Fourier inverse transform which is a reciprocal of the Fourier transform of h or a calculation using a result of the Fourier inverse transform which is the reciprocal of the Fourier transform of h .

14. (previously presented) The image pickup apparatus according to claim 10, further comprising:
a processing amount calculating section for calculating a calculation processing amount required for correcting the shaking motion in the video information.

15. (previously presented) The image pickup apparatus according to claim 14, wherein
when the calculation processing amount or a shaking motion amount exceeds a predetermined value, a display indicating an exceeding situation is made on a display section and/or a sound indicating an exceeding situation is generated from a speaker.

16. (previously presented) The image pickup apparatus according to claim 14, wherein
when the calculation processing amount exceeds a predetermined value, the video information which is not subjected to the correction of the shaking motion is output, and
when the calculation processing amount is within a predetermined range, corrected video information which is subjected to the correction of the shaking motion in the video information is output.

17. (previously presented) The image pickup apparatus according to claim 10, wherein
at a specific time after displaying the video information on a display section, the corrected video information is displayed on the display section.

18. (previously presented) The image pickup apparatus according to claim 17, wherein
time at which the calculation processing for the correction of the shaking motion in the electronic shaking motion correcting section is completed is used as the specific time.

19. (previously presented) The image pickup apparatus according to claim 10, further comprising:
a maximum shaking motion amount calculating section for receiving the corrected video information from the shaking motion correcting section, and for calculating a maximum shaking motion amount of the shaking motion in each direction; and

a trimming section for trimming the corrected video information in accordance with the maximum shaking motion amount, so as to generate trimmed corrected video information.

20. (previously presented) The image pickup apparatus according to claim 19, further comprising:
a setting section capable of setting a first trimming mode or a second trimming mode, wherein
in the first trimming mode, the trimming section trims the corrected video information in accordance with the maximum shaking motion amount, so as to generate a first trimmed corrected video information, and

in the second trimming mode, the trimming section trims the first trimmed corrected video information, as a center of a pixel corresponding to a center pixel of the first trimmed corrected video information, so as to generate a second trimmed corrected video information, the center pixel being a pixel located at a center of the video information in each direction.

21. (previously presented) The image pickup apparatus according to claim 1, further comprising:
a mechanical shaking motion correcting section for mechanically correcting the shaking motion of the image pickup apparatus in accordance with the shaking motion detection signal, so as to obtain corrected video information which is subjected to the correction of the shaking motion in the video information by an actual shaking motion correction amount, wherein

the locus calculating section obtains, as the locus information, information indicating a change during a predetermined period of time in a difference between the shaking motion detection signal and the actual shaking motion correction amount.

22. (previously presented) The image pickup apparatus according to claim 21, wherein
the locus information is in an Exif format.

23. (previously presented) The image pickup apparatus according to claim 21, wherein
the mechanical shaking motion correcting section mechanically corrects the shaking motion of the image pickup apparatus in accordance with the shaking motion detection signal, so as to obtain a first corrected video information which is subjected to the correction of the shaking motion in the video information by a first shaking motion correction amount,

the locus calculating section obtains, as the locus information, information indicating a change in a remaining shaking motion amount during a predetermined period of time, the remaining shaking

motion amount indicating a difference between the actual shaking motion correction amount and the first shaking motion correction amount, and

the image pickup apparatus further comprises:

an electronic shaking motion correcting section for performing a calculation processing on the locus information and the first corrected video information, so as to obtain a second corrected video information which is subjected to the correction of the shaking motion in the first corrected video information by a second shaking motion correction amount.

24. (previously presented) The image pickup apparatus according to claim 23, wherein the calculation processing includes a Fourier transform, a Fourier inverse transform, or a processing using a two-dimensional filter.
25. (previously presented) The image pickup apparatus according to claim 23, wherein the locus information includes a locus function h , and the calculation processing includes a calculation of a Fourier transform of h or a calculation using a result of the Fourier transform of h , or the calculation processing includes a calculation of a Fourier inverse transform which is a reciprocal of the Fourier transform of h or a calculation using a result of the Fourier inverse transform which is the reciprocal of the Fourier transform of h .
26. (previously presented) The image pickup apparatus according to claim 21, wherein the mechanical shaking motion correcting section calculates the first shaking motion correction amount based on positional information of a lens which is a part of the image forming section.
27. (previously presented) The image pickup apparatus according to claim 21, wherein the mechanical shaking motion correcting section calculates the first shaking motion correction amount based on the shaking motion detection signal and a shaking motion control characteristic of the mechanical shaking motion correcting section.
28. (previously presented) The image pickup apparatus according to claim 1, wherein the shaking motion detecting section includes: a first shaking motion detecting section for detecting a shaking motion in a pitch direction and a shaking motion in a yaw direction among the shaking motions of the image pickup apparatus; and a second shaking motion detecting section for

detecting a shaking motion in a roll direction among the shaking motions of the image pickup apparatus,

the locus calculating section obtains, as the locus information, information indicating a change during a predetermined period of time in a detection signal output from the second shaking motion detecting section, and

the image pickup apparatus further comprises:

a mechanical shaking motion correcting section for obtaining a first corrected video information which is subjected to the correction of the shaking motion in the pitch direction and the correction of the shaking motion in the yaw direction in accordance with a detection signal output from the first shaking motion detecting section.

29. (previously presented) The image pickup apparatus according to claim 28, further comprising:
a section for adding the locus information to the corrected video information for output, or for recording the locus information onto a recording medium.

30. (previously presented) The image pickup apparatus according to claim 29, wherein
the locus information is in an Exif format or a format similar to the Exif format.

31. (previously presented) The image pickup apparatus according to claim 28, further comprising:
an electronic shaking motion correcting section for obtaining a second corrected video information, which is subjected to the correction of the shaking motion in the first corrected video information, by performing a calculation processing on locus information in the roll direction and the first corrected video information.

32. (previously presented) The image pickup apparatus according to claim 31, wherein
the calculation processing includes a Fourier transform, a Fourier inverse transform, or a processing using a two-dimensional filter.

33. (previously presented) The image pickup apparatus according to claim 31, wherein
the locus information includes a locus function h , and
the calculation processing includes a calculation of a Fourier transform of h or a calculation using a result of the Fourier transform of h , or

the calculation processing includes a calculation of a Fourier inverse transform which is a reciprocal of the Fourier transform of h or a calculation using a result of the Fourier inverse transform which is the reciprocal of the Fourier transform of h .

34. (Original) A product package comprising an image pickup apparatus and a recording medium, wherein

the image pickup apparatus includes:

a shaking motion detecting section for detecting a shaking motion of the image pickup apparatus and for outputting a shaking motion detection signal indicating the shaking motion of the image pickup apparatus;

an image forming section for forming an optical image by focusing light incident to the image pickup apparatus;

an image pickup section for converting the optical image formed by the image forming section into electric video information;

a locus calculating section for obtaining locus information indicating a locus of the shaking motion of the image pickup apparatus based on at least the shaking motion detection signal output from the shaking motion detecting section; and

an outputting section for adding the locus information to the video information to output image information, and

the recording medium has a program recorded therein, the program is for causing a computer to execute a processing, the processing includes:

receiving the image information;

separating the image information into the locus information and the video information; and

obtaining corrected video information, which is subjected to the correction of the shaking motion in the video information, by performing a calculation processing on the locus information and the video information.

35. (previously presented) The product package according to claim 34, wherein the locus information is in an Exif format.

36. (previously presented) The product package according to claim 34, wherein the calculation processing includes a Fourier transform, a Fourier inverse transform, or a processing using a two-dimensional filter.

37. (previously presented) The product package according to claim 34, wherein
the locus information includes a locus function h , and
the calculation processing includes a calculation of a Fourier transform of h or a calculation
using a result of the Fourier transform of h , or
the calculation processing includes a calculation of a Fourier inverse transform which is a
reciprocal of the Fourier transform of h or a calculation using a result of the Fourier inverse transform
which is the reciprocal of the Fourier transform of h .
38. (previously presented) The product package according to claim 34, wherein
the locus information is a weighted locus or a point spread function.
39. (Original) A product package comprising an image pickup apparatus and a recording medium,
wherein
the image pickup apparatus includes:
a shaking motion detecting section for detecting a shaking motion of the image pickup
apparatus and for outputting a shaking motion detection signal indicating the shaking motion of the
image pickup apparatus;
an image forming section for forming an optical image by focusing light incident to the image
pickup apparatus;
an image pickup section for converting the optical image formed by the image forming section
into electric video information;
a locus calculating section for obtaining locus information indicating a locus of the shaking
motion of the image pickup apparatus based on at least the shaking motion detection signal output
from the shaking motion detecting section;
a mechanical shaking motion correcting section for mechanically correcting the shaking motion
of the image pickup apparatus in accordance with the shaking motion detection signal, so as to obtain
corrected video information which is subjected to the correction of the shaking motion in the video
information by an actual shaking motion correction amount; and
an outputting section for adding the locus information to the video information to output image
information,
the locus calculating section obtains, as the locus information, information indicating a change
during a predetermined period of time in a difference between the shaking motion detection signal and
the actual shaking motion correction amount, and

the recording medium has a program recorded therein, the program is for causing a computer to execute a processing, the processing includes:

receiving the image information;
separating the image information into the locus information and the video information; and
obtaining corrected video information which is subjected to the correction of the shaking motion in the video information, by performing a calculation processing on the locus information and the video information.

40. (previously presented) The product package according to claim 39, wherein the locus information is in an Exif format.

41. (previously presented) The product package according to claim 39, wherein the calculation processing includes a Fourier transform, a Fourier inverse transform, or a processing using a two-dimensional filter.

42. (previously presented) The product package according to claim 39, wherein the locus information is a weighted locus or a point spread function.

43. (previously presented) A semiconductor integrated circuit comprising:
a locus calculating section for obtaining locus information indicating a locus of a shaking motion of an image pickup apparatus based on at least a shaking motion detection signal output from a shaking motion detecting section for detecting the shaking motion of the image pickup apparatus, wherein the locus calculating section determines whether or not an amount of temporal change in the shaking motion of the image pickup apparatus is larger than a predetermined threshold value, and determines a number of samples in accordance with the determination result.

44. (previously presented) The semiconductor integrated circuit according to claim 43, further comprising:

an electronic shaking motion correcting section for obtaining corrected video information which is subjected to the correction of the shaking motion in the video information, by performing a calculation processing on the locus information and the video information.

45. (previously presented) The semiconductor integrated circuit according to claim 43, further comprising:

a mechanical shaking motion correcting section for mechanically correcting the shaking motion of the image pickup apparatus in accordance with the shaking motion detection signal, so as to obtain corrected video information which is subjected to the correction of the shaking motion in the video information by an actual shaking motion amount, wherein

the locus calculating section obtains, as the locus information, information indicating a change during a predetermined period of time in a difference between the shaking motion detection signal and the actual shaking motion correction amount.

46. (previously presented) The semiconductor integrated circuit according to claim 43, wherein the shaking motion detecting section includes: a first shaking motion detecting section for detecting a shaking motion in a pitch direction and a shaking motion in a yaw direction among the shaking motions of the image pickup apparatus; and a second shaking motion detecting section for detecting a shaking motion in a roll direction among the shaking motions of the image pickup apparatus,

the locus calculating section obtains, as the locus information, information indicating a change during a predetermined period of time in a detection signal output from the second shaking motion detecting section, and

the semiconductor integrated circuit further comprises:

a mechanical shaking motion correcting section for obtaining a first corrected video information which is subjected to the correction of the shaking motion in the pitch direction and the correction of the shaking motion in the yaw direction in accordance with a detection signal output from the first shaking motion detecting section.